

Hanasaki MV5000 4T Motorcycle Oil SAE 10W-40

Superior Performance Four-Stroke Motorcycle Engine Oil

Product Description

Hanasaki MV5000 4T Motorcycle Oil SAE 10W-40 is a super high-performance multigrade engine oil specially designed for use in scooters fitted with four-stroke engines without wet clutch. Formulated with advance Japanese additive technology and high-quality hydro-refined base oils, MV5000 offers ultimate engine protection to motorcycle engines operating under very severe conditions. This product is suitable for all types of gasoline fuels, leaded or unleaded and biofuels.

Hanasaki MV5000 4T Motorcycle Oil SAE 10W-40 provides the following benefits to its users:

- 1) Reduced-friction formulation provides real fuel saving performance: up to 2.5% versus 20W-50 JASO MA2 oils and up to 2.0% versus 10W-40 JASO MA2 oils.
- 2) Unique additive chemistry ensures excellent protection against engine wear
- 3) Outstanding protection against engine deposit, rust and corrosion
- 4) Outstanding viscosity control
- 5) Excellent low temperature properties
- 6) High compatibility with rubber parts in engines (gasket and seal)
- 7) Extended service life

Performance Standards

API SJ, JASO MB

Typical Properties

SAE Grade	10W-40
Viscosity @ 40°C (ASTM D445) , cst	106
Viscosity @ 100°C (ASTM D445) ,cst	14.8
Viscosity Index (ASTM 2270)	145
Total Base Number (ASTM D2896) , mgKOH/g	7.5
Pour Point (ASTM D97) , °C	-33
Flash Point (ASTM D92) , °C	220
Density @ 15°C (ASTM D4052) , kg/l	0.855

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS is available upon request through your sales contact at Hanasaki. This product should not be used for purposes other than its intended use. When disposing of used product, please take care to protect the environment.