

Hanasaki Genset SAE 30

Premium Quality 8 TBN Engine Oil for Generator

Product Description

Hanasaki Genset SAE 30 is a premium quality diesel engine oil specially designed for the severe application of generators. The product is formulated with high quality baseoil and advance additives to deliver superior protection of generator against excessive deposit, wear, corrosion and rust.

Hanasaki Genset SAE 30 provides the following benefit to its uses:

- 1) Excellent detergency and dispersancy additive chemistry that significantly reduces the formation of lacquer, varnish, sludge and other deposits in the engine system
- 2) Strong resistance against oil oxidation under high temperature operation
- 3) Strong anti-rust and anti-corrosion properties to protect against corrosion from arduous acidic by-products of combustion
- 4) Good anti-wear properties to ensure long service life of moving parts
- 5) Stable lubricating film guarantees a long engine life
- 6) Good flow property in low temperature climate (0 to 15°C)

Performance Standards

API CF, MIL-L-2104D, MIL-46152C

Typical Properties

SAE Grade	30
Viscosity @ 40°C (ASTM D445), cst	104
Viscosity @ 100°C (ASTM D445), cst	11.8
Viscosity Index (ASTM 2270)	102
Total Base Number (ASTM D2896), mgKOH/g	8
Pour Point (ASTM D97), °C	-15
Flash Point (ASTM D92), °C	230
Density @ 15°C (ASTM D4052), kg/l	0.895

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended applications and the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS is available upon request through your sales contact at Hanasaki. This product should not be used for purposes other than its intended use. When disposing of used product, please take care to protect the environment.